

## SEI-T8322TI



**Bullet IP, 8Mpxl, 2.8-12mm MOTOR., ICR, WDR 120dB, LEDs 50-70mt, IP67/IK10, POE, H.265, Face Detection, ADVANCED VCA A**

- 4K Resolution for super detailed images
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built-in SD card reader for message recording in case of no answer
- Block of access after multiple login failed tentatives
- System Log preserved after system reset
- Request to modify password at first login
- AES128 encryption on local SD recording

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2.8" Progressive Scan CMOS
<b>Pixels - Total</b>	3840 (H)x 2160 (V), 25fps
<b>Video Resolution</b>	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288) , 3840 x 2160 (25fps), 4MP (2592x1520)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto, IR-cut filter removable (ICR)
<b>Sensitivity Colour</b>	0.01 lux @ F1.2, 0.015 Lux F1.4
<b>Sensitivity B/W</b>	0 Lux LED IR on
<b>Lens Focal Length</b>	2.8 ~ 12 mm Motorized @F1.4
<b>Iris Operation</b>	Auto iris (DC)
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	70 m
<b>WDR</b>	WDR Pro 120dB
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	H.264, MJPEG, H.265, H.264+, Triple Streaming
<b>ONVIF compliant</b>	Profile S, Profile G
<b>Advanced Video Analytics</b>	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
<b>Intelligent Video Analytics</b>	Tampering, Motion Detection, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
<b>Max. Users</b>	10
<b>SD memory</b>	supports up to 128 GB capacity of micro TF Card
<b>Functions</b>	LDC (Lens Distortion Correction)
<b>Alarm</b>	Input: 1 / Output: 1
<b>Audio Inputs</b>	1 CH, Line in
<b>Audio Outputs</b>	1 CH, RCA, None
<b>Audio Compression</b>	G.711 a/u
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP

## Technical Specifications

<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Interfaces</b>	RS-485
<b>Supply Voltage</b>	12 Vdc / PoE (IEEE 802.3af)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30° C ~ +60° C
<b>Humidity</b>	less than 95%, non condensing
<b>Dimensions ( W x H x D)</b>	88.9 x 100.3 x 279.5 mm - 3.5 x 3.95 x 11 In
<b>Power Consumption (W)</b>	12
<b>Weight</b>	1.04 kg - 2.29 lbs