

# R1125T-N

## Stubby press-fit recessed mount contact with terminals and "Mini-Max" magnet, white

### Stubby "Press-Fit" contact

---

The Sentrol R1125T series "Stubby" Press-Fit magnetic contacts are a 9 mm switch designed specifically for applications where space is limited. The short length makes it ideal for thin-framed windows and doors where longer units cannot be used. Press fit ribs on the housing make for quick, easy installation. The Mini-Max magnet can be fitted where almost no space is available to mount a normal magnet.

### Easy installation

---

Switch is hermetically sealed reed switch, which is potted using exclusive polyurethane potting compound into the switch housing. Switch is drill-mounted in wood or aluminum with a suitable adhesive. The Alnico V Mini-Max magnet mounts with adhesive take or a stainless steel screw. The switch housing has three fins to press-fit against the mounting hole.

### Durability and dependability

---

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

### High quality components and materials

---

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



### Dettagli

---

- Rare-earth magnet technology delivers powerful magnetic force
- Ideal for PVC windows and doors
- Easy to install in any situation
- Magnet mounts easily with glue, double-sided tape, or stainless-steel screw

# R1125T-N

Stubby press-fit recessed mount contact with terminals and "Mini-Max" magnet, white

## Specifiche tecniche

---

### Generale

Application type	Montaggio ad incasso
Contact type	NC
Connectivity	Screw terminals

### Cablato / senza fili

Wired-wireless	Cablato
Operating gap	13 mm (max.)

### Fisico

Dimensions magnet	9 x 3 mm (Ø x L)
Dimensions contact / sensor	9 x 27 mm (Ø x L)
Colour	Bianco



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita [it.firesecurityproducts.com](http://it.firesecurityproducts.com) online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:53